NASPI WG Panel Session

PG&E Experience and Lessons Learned

NASPI Meeting November 4, 2020 Sherman Chen PG&E

1

Initial Synchrophasor Deployment at PG&E

- Installed for WISP with DOE Cost Share (2009)
- PMUs in existing RAS relays
- 202 PMUs, 101 redundant measurement locations (line voltages and currents)
- 24 Substation PDCs, 12 redundant locations
- 4 control center PDCs, 2 redundant locations
- Architecture is NERC CIP compliant (Operational Data Network, PCAs vs BCAs)
- 61850 communications protocol between PMUs and substation PDCs, and between substation PDCs and control center PDCs (Field Gateways)
- 2 WISP Gateways delivering data to PeakRC


Enhancements

- Installed 3 PMUs on generator terminals at 2x1 combined cycle power plant (MOD-26 & MOD-27)
- Established Transmission Operations Synchrophasor Test Lab (TOSTL)
- Initial deployment had low availability and high latency, changed communications protocol from substation PDCs to control center PDCs to 37.118 resulting in greatly enhanced data availability
- Replaced all substation GPS clocks
- Added 6 PMUs monitoring 500 kV bus voltages and line currents
- Standardized on general purpose PMU/PDC appliance for future PMU/PDC installations monitoring bus voltages and line currents
- Established PMU/PDC lifecycle program
- 2 WISP Gateways sending data to CAISO RC West via managed ethernet 10Mbps

Future Enhancements

- All lifecycle PMU/PDCs will stream 37.118 to control center Field Gateways and measure bus voltages and line currents
- PMUs will be independent of substation relays
- Improve system-wide availability
- Improve access to archived data
- Establish OSISoft PI archive on corporate network
- Install PMUs on 500 kV tie-lines to two STATCOMs (Gates and Round Mountain)
- Install PMUs on 500 kV tie-lines to the 300 MW/1200 MWh Dallas Battery Energy Storage System at Moss Landing (world's largest battery energy storage project)
- Install PMUs on all tie-lines with other utilities (BAL-003)

Neighboring Electric Utilities and Balancing Authorities



Archives

- Original archives openHistorian and PhasorPoint distributed among multiple servers
- Future archives moving to a combination of openHistorian and OSISoft PI (150 TB, 3 years)
- OSISoft PI will be deployed on corporate network to make data available enterprise wide (PRC-002-2, MOD-033)

Lessons Learned

- Utilize 37.118 until there is a new standard
- Install on NERC CIP-compliant network even if applications will not be used by grid operators initially
- Install reliable GPS clocks
- Utilize PMU/PDCs independent of substation relays
- Establish support network including IT system administrators, network operations, communications technicians, protection engineers, automation engineers, and substation electrical technicians

7

Data Availability Dashboards

?

🏂 Field PDC Daily Availability - Graf 🗙 🕂						
 ← → C ① localhost:8180/grafana/d/gCHhyQ2Zk/field-pdc-daily-availability?org1d=1&refresh=2h ☆ PDC Daily Availabili 						
Ø	🚼 Availability > Field PDC Daily Availability - 🕑 🗈 🌞 🖵 💿 Last 90 days -					uhl ☆ 🖆 🖺 🎄 🖵 ⊙Last 90 days - Q 🕃 2h -
+	A Cinnabar	B Cinnabar	ය A Diablo	B Diablo	A Eastbay B Eastbay	A Fresno B Fresno
	100.00%	99.90%	100.00%	100.00%	98.95% 100.00%	97.72% 100.00%
Ļ	යි A Los Banos	B Los Banos	A Midway	B Midway	A Pittsburg B Pittsburg	A Round Mt. B Round Mt.
*	100.00%	100.00%	100.00%	100.00%	100.00% 100.00%	100.00% 100.00%
	ය Santa Rosa	ය B Santa Rosa	A Table Mt.	B Table Mt.	A Tesla B Tesla	🖾 A Vaca 🖾 B Vaca
	100.00%	100.00%	0%	100.00%	99.16% 100.00%	100.00% 100.00%
	ABB METCALF	ABB ROUND MT	C ABB TABLE MT	B ABB VACA DIXON	A Moss Lndng SEL 3355 B Moss Lndng SEL 3355	
	100.00%	100.00%	100.00%	100.00%	100.00% 100.00%	